



## FOR30/40 Product Datasheet

### General Information

**FOR30/40** is special Distilled Tall Oil (DTO) product with a special combination of fatty and rosin acids. **FOR30/40** is an excellent raw material in various applications for example it can be used in metal working fluids, oil field chemicals, soaps, cleaners and alkyd resins.

### Specification of FOR30/40

Analysis	Value	Method
Colour Gardner, photometer	max. 10	ASTM D 6166-97
Free rosin acids, %	30 – 40	SCAN-T 14:78
Unsaponifiabiles, %	7	SCAN-T 13:74

### Typical analyses of FOR30/40

Analysis	Value	Method
Acid value	187	SCAN-T 11:72
Cloud point, °C	6	ASTM D 2500-99
Colour Gardner, photometer	7	ASTM D 6166-97
Density at 20 °C, kg/m <sup>3</sup>	955	SCAN-T 2:65
Flash point, closed cup, °C	200	ASTM D 93-00
Free fatty acids, %	59	ASTM D 5974-00
Free rosin acids, %	33	SCAN-T 14:78
Refractive index at 20 °C	1,497	SCAN-T 1:65
Saponification value	190	SCAN-T 12:72
Unsaponifiabiles, %	5	SCAN-T 13:74
Viscosity at 20 °C, mPas	200	ASTM D 2196-99

### Product handling

**FOR30/40** should be delivered at around 60 °C and the recommended minimum storage temperature is 50 °C. If **FOR30/40** is subjected to cold temperatures during storage or transportation it may become cloudy or show some precipitation or crystallization. This is a normal characteristic and not a defect. If affected, the material should be gently heated to around 85 °C and circulated or agitated to restore the clear and bright condition.

### Delivery form

Preferably bulk liquid in road tanker, rail tank wagon, ISO-container. Delivery in flexitank, steel drums and IBCs is possible subject to product handling considerations above.

**EINECS number** 232-304-6  
**CAS number** 8002-26-4  
**CN-code** 38030090

PDS **FOR30/40** 001 August 2010

In all applications of **FOR30/40** it is the sole responsibility of the buyer to respect and comply with any valid intellectual property rights of third parties.